SUBSONIC-SONIC LIMIT OF APPROXIMATE SOLUTIONS TO MULTIDIMENSIONAL STEADY EULER EQUATIONS

GUI-QIANG CHEN, FEI-MIN HUANG, AND TIAN-YI WANG

ABSTRACT. A compactness framework is established for approximate solutions to subsonic-sonic flows governed by the steady full Euler equations for compressible fluids in arbitrary dimension. The existing compactness frameworks for the two-dimensional irrotational case do not directly apply for the steady full Euler equations in higher dimensions. The new compactness framework we develop applies for both non-homentropic and rotational flows. One of our main observations is that the compactness can be achieved by using only natural weak estimates for the mass balance and the vorticity, along with the Bernoulli law and the entropy relation, through a more delicate analysis on the phase space. As direct applications, we establish two existence theorems for multidimensional subsonic-sonic full Euler flows through infinitely long nozzles.

1. Introduction

The full Euler equations for steady compressible flows in \mathbb{R}^n read

$$\begin{cases} \operatorname{div}(\rho u) = 0, \\ \operatorname{div}(\rho u \otimes u + pI) = 0, \\ \operatorname{div}(\rho uE + up) = 0, \end{cases}$$
(1.1)

where $x = (x_1, \dots, x_n) \in \mathbb{R}^n, n \geq 2, u = (u_1, \dots, u_n) \in \mathbb{R}^n$ is the fluid velocity, and

$$q := |u| = \left(\sum_{i=1}^{n} u_i^2\right)^{1/2}$$

is the speed, while ρ , p, and E represent the density, pressure, and total energy, respectively, and I is the $n \times n$ unit matrix. The nonnegative quantities ρ , q, p, and E are not independent.

For ideal polytropic gas,

$$E = \frac{q^2}{2} + \frac{p}{(\gamma - 1)\rho}$$

with adiabatic exponent $\gamma > 1$. In this case, the Bernoulli law is written as

$$\frac{q^2}{2} + h(\rho, p) = B, (1.2)$$

where $h(\rho, p) = \frac{\gamma p}{(\gamma - 1)\rho}$ is the enthalpy, and B is a Bernoulli function determined by appropriate additional conditions (such as boundary conditions and/or asymptotic conditions at infinity). The sound speed of the flow is

$$c = \sqrt{\frac{\gamma p}{\rho}},\tag{1.3}$$

and the Mach number is defined as

$$M = \frac{q}{c}. (1.4)$$

Date: July 28, 2015.

²⁰¹⁰ Mathematics Subject Classification. 35Q31; 35M30; 35L65; 76N10; 76G25; 35B40; 35D30.

Key words and phrases. Multidimensional, subsonic-sonic limit, steady flow, full Euler equations, homentropic, rotation, compactness framework, strong convergence, exact solutions, approximate solutions.

Then, for a fixed Bernoulli function B, there is a critical speed $q_{\rm cr} = \sqrt{2\frac{\gamma-1}{\gamma+1}B}$ such that, when $q \leq q_{\rm cr}$, the flow is subsonic-sonic (that is, $M \leq 1$); otherwise, it is supersonic (that is, M > 1).

When the flow is homentropic, the pressure is a function of the density, and (1.1) then reduces to

$$\begin{cases} \operatorname{div}(\rho u) = 0, \\ \operatorname{div}(\rho u \otimes u + pI) = 0. \end{cases}$$
(1.5)

As usual, we require

$$p'(\rho) > 0$$
, $2p'(\rho) + \rho p''(\rho) > 0$ for $\rho > 0$,

which include the γ -law flows with $p = \kappa \rho^{\gamma}$, $\gamma > 1$ and $\kappa > 0$, and the isothermal flows with $p = \kappa \rho$; see [12]. In this case, the Bernoulli law has the same formula as (1.2), while the enthalpy $h(p(\rho), \rho) = h(\rho)$ with $h'(\rho) = \frac{p'(\rho)}{\rho}$. The sound speed of the flow is $c = \sqrt{p'(\rho)}$, and the Mach number is defined as $M = \frac{q}{c}$. Then, for a fixed Bernoulli function B, the condition $2p'(\rho) + \rho p''(\rho) > 0$ for $\rho > 0$ implies the existence of a unique critical speed $q_{\rm cr} = q_{\rm cr}(B)$ so that the flow can be classified by subsonic-sonic or supersonic by $q \leq q_{\rm cr}$ or $q > q_{\rm cr}$, respectively.

It is well known that the steady Euler equations for compressible fluids are of compositemixed type, which is determined by the Mach number M. That is, the system can be reduced to a system such that two of the equations are elliptic-hyperbolic mixed: elliptic when M < 1and hyperbolic when M > 1, while the other n equations are hyperbolic. For the homentropic case, there are two mixed characteristics and n-1 hyperbolic characteristics.

During the 1950s, the effort on system (1.5) was focused mainly on the irrotational case, namely when u is constrained to satisfy the additional equation $\operatorname{curl} u = 0$. Since the equations of uniform subsonic flow possess ellipticity, solutions have better regularity than those corresponding to transonic or supersonic flow. The airfoil problem for irrotational, two-dimensional subsonic flow was solved; cf. Frankl-Keldysh [22], Shiffman [28], Bers [3], and Finn-Gilbarg [20]. The first result for three-dimensional subsonic flow past an obstacle was given by Finn and Gilbarg [21] under some restrictions on the Mach number. Dong [15] and Dong-Ou [16] extended the results to the maximum Mach number M < 1 for the arbitrarily dimensional case. Also see Du-Xin-Yan [18] for the construction of a smooth uniform subsonic flow in an infinitely long nozzle in \mathbb{R}^n , $n \geq 2$.

For the rotational case, the global existence of homentropic subsonic flow through two-dimensional infinitely long nozzles was proved in Xie-Xin [32]. The result was also extended to the two-dimensional periodic nozzles in Chen-Xie [5] and to axisymmetric nozzles in Du-Duan [17]. For the full Euler flow, the first result was given by Chen-Deng-Xiang [7] for two-dimensional infinitely long nozzles. Bae [1] showed the stability of contact discontinuities for subsonic full Euler flow in the two-dimensional, infinitely long nozzles. Duan-Luo [19] recently considered the axisymmetric nozzle problem for the smooth subsonic flow.

On the other hand, few results are currently known for the cases of subsonic-sonic flow and transonic flow, since the uniform ellipticity is lost and shocks may be present. That is, smooth solutions may not exist. Instead, one must consider weak solutions. Morawetz [24, 25] introduced an approach via compensated compactness to analyze irrotational steady flow of the Euler equations. Indeed, Morawetz established a compactness framework under the assumption that the solutions are free of stagnation points and cavitation points. Morawetz's result has been improved by Chen-Slemrod-Wang [10], who have shown that the approximate solutions away from cavitation are constructed by a viscous perturbation.

The compactness framework for subsonic-sonic irrotational flow allowing for stagnation in two dimensions was due to Chen-Dafermos-Slemrod-Wang [9] by combining the mass conservation, momentum, and irrotational equations. The key observation in [9] is that the two-dimensional steady flow can be regarded as a one-dimensional unsteady system of conservation laws, that is, one of the spatial variables can be regarded as the time variable, so that the divcurl lemma can be applied to the two momentum equations. In fact, the momentum equations are first employed in [9] to reduce the support of the corresponding Young measure to two points, and then the irrotational equation and the mass equation are used to reduce the Young measure to a Dirac measure. Using a similar idea, Xie-Xin [30] investigated the subsonic-sonic limit of the two-dimensional irrotational, infinitely long nozzle problem. Later, in [31], they extended the result to the three-dimensional axisymmetric flow through an axisymmetric nozzle. The compactness framework in the multidimensional irrotational case was established in Huang-Wang-Wang [23].

The compactness framework established for irrotational flow no longer applies directly for the steady full Euler equations in \mathbb{R}^n with $n \geq 2$. When $n \geq 3$, the equations cannot be reduced to a one-dimensional system of conservation laws. More importantly, the div-curl lemma is no longer valid for the momentum equations, due to the presence of linear characteristics. One of our main observations is that it is still possible to achieve the same compactness result, *i.e.*, to reduce the Young measure to a Dirac measure, by using only natural weak estimates for the mass balance and the vorticity, along with the Bernoulli law and entropy relation, through a more delicate analysis on the phase space. In particular, the Bernoulli function and entropy function play a key role in our proof. We then establish a compactness framework for approximate solutions for steady full Euler flows in arbitrary dimension.

The rest of this paper is organized as follows. In Section 2, we establish the compactness framework for subsonic-sonic approximate solutions to subsonic-sonic flows governed by the steady full Euler equations for compressible fluids in \mathbb{R}^n with $n \geq 2$, as well as by the steady homentropic Euler equations with weaker conditions. In Sections 3–4, we give two direct applications of the compactness framework to establish the existence of subsonic-sonic full Euler flow through infinitely long nozzles in \mathbb{R}^n with $n \geq 2$.

2. Compactness Framework for Approximate Steady Full Euler Flows

In this section, we establish the compensated compactness framework for approximate solutions of the steady full Euler equations in \mathbb{R}^n with $n \geq 2$ with the form:

$$\begin{cases}
\operatorname{div}(\rho^{\varepsilon}u^{\varepsilon}) = e_{1}(\varepsilon), \\
\operatorname{div}(\rho^{\varepsilon}u^{\varepsilon} \otimes u^{\varepsilon} + p^{\varepsilon}I) = e_{2}(\varepsilon), \\
\operatorname{div}(\rho^{\varepsilon}u^{\varepsilon}E^{\varepsilon} + u^{\varepsilon}p^{\varepsilon}) = e_{3}(\varepsilon),
\end{cases}$$
(2.1)

where $e_1(\varepsilon)$, $e_2(\varepsilon) = (e_{21}(\varepsilon), \dots, e_{2n}(\varepsilon))^{\top}$, and $e_3(\varepsilon)$ are sequences of functions depending on the parameter ε .

Let a sequence of functions $\rho^{\varepsilon}(x)$, $u^{\varepsilon}(x) = (u_1^{\varepsilon}, \dots, u_n^{\varepsilon})(x)$, and $p^{\varepsilon}(x)$ be defined on an open subset $\Omega \subset \mathbb{R}^n$ such that the following qualities:

$$q^{\varepsilon} := |u^{\varepsilon}| = \sqrt{\sum_{i=1}^{n} (u_i^{\varepsilon})^2}, \quad c^{\varepsilon} := \sqrt{\frac{\gamma p^{\varepsilon}}{\rho^{\varepsilon}}}, \quad M^{\varepsilon} := \frac{q^{\varepsilon}}{c^{\varepsilon}},$$
 (2.2)

$$B^{\varepsilon} := \frac{(q^{\varepsilon})^2}{2} + \frac{\gamma p^{\varepsilon}}{(\gamma - 1)\rho^{\varepsilon}}, \qquad S^{\varepsilon} := \frac{\gamma p^{\varepsilon}}{(\gamma - 1)(\rho^{\varepsilon})^{\gamma}}$$
 (2.3)

can be well defined and satisfy the following conditions:

(A.1). $M^{\varepsilon} \leq 1$ a.e. in Ω ;

(A.2). S^{ε} and B^{ε} are uniformly bounded and, for any compact set K, there exists a uniform constant c(K) such that $\inf_{x \in K} S^{\varepsilon}(x) \geq c(K) > 0$. Moreover, $(S^{\varepsilon}, B^{\varepsilon}) \to (\overline{S}, \overline{B})$ a.e. in Ω ;

(A.3). curl u^{ε} and $e_1(\varepsilon)$ are in a compact set in $W_{loc}^{-1,p}$ for some 1 .

Then we have

Theorem 2.1 (Compensated compactness framework for the full Euler case). Let a sequence of functions $\rho^{\varepsilon}(x)$, $u^{\varepsilon}(x) = (u_1^{\varepsilon}, \dots, u_n^{\varepsilon})(x)$, and $p^{\varepsilon}(x)$ satisfy conditions (A.1)–(A.3). Then there exists a subsequence (still labeled) $(\rho^{\varepsilon}, u^{\varepsilon}, p^{\varepsilon})(x)$ such that

$$\rho^{\varepsilon}(x) \to \rho(x), \quad u^{\varepsilon}(x) \to (u_1, \cdots, u_n)(x), \quad p^{\varepsilon}(x) \to p(x) \quad a.e. \text{ in } x \in \Omega \text{ as } \varepsilon \to 0,$$

and

$$M(x) := \frac{q(x)}{c(x)} \le 1$$
 a.e. $x \in \Omega$.

Proof. We divide the proof into three steps.

Step 1. The strong convergence of $(\rho^{\varepsilon}, p^{\varepsilon})$ follows from the strong convergence of $q^{\varepsilon} = |u^{\varepsilon}|$. We employ (2.3) to obtain

$$\frac{(q^{\varepsilon})^2}{2} + S^{\varepsilon}(\rho^{\varepsilon})^{\gamma - 1} = B^{\varepsilon}. \tag{2.4}$$

From these, the three variables ρ^{ε} , p^{ε} , and q^{ε} are determined by one of them. In other words, the pressure p^{ε} and density ρ^{ε} can be regarded as functions of q^{ε} through $(B^{\varepsilon}, S^{\varepsilon})$ with

$$\rho^{\varepsilon} = \rho(q^{\varepsilon}; B^{\varepsilon}, S^{\varepsilon}) = \left(\frac{2B^{\varepsilon} - (q^{\varepsilon})^{2}}{2S^{\varepsilon}}\right)^{\frac{1}{\gamma - 1}},\tag{2.5}$$

$$p^{\varepsilon} = p(q^{\varepsilon}; B^{\varepsilon}, S^{\varepsilon}) = \frac{\gamma - 1}{2\gamma} \frac{\left(2B^{\varepsilon} - (q^{\varepsilon})^{2}\right)^{\frac{\gamma}{\gamma - 1}}}{\left(2S^{\varepsilon}\right)^{\frac{1}{\gamma - 1}}}.$$
 (2.6)

Since $(B^{\varepsilon}, S^{\varepsilon})$ strongly converge to $(\overline{B}, \overline{S})$ a.e., the strong convergence of the density ρ^{ε} and pressure p^{ε} becomes a nature consequence of the strong convergence of the speed q^{ε} .

Step 2. The H_{loc}^{-1} -compactness. From the uniform boundedness of the Bernoulli function B^{ε} and the subsonic-sonic condition $M^{\varepsilon} \leq 1$, it is easy to see

$$q^{\varepsilon} \le \sup_{\varepsilon} \sqrt{2 \frac{\gamma - 1}{\gamma + 1} B^{\varepsilon}},$$

which implies the uniform boundedness of the velocity $u^{\varepsilon}(x) = (u_1^{\varepsilon}, \dots, u_n^{\varepsilon})(x)$. This shows that

$$(\operatorname{curl} u^{\varepsilon})_{ij} = \partial_{x_i} u_j^{\varepsilon} - \partial_{x_j} u_i^{\varepsilon}$$
 is bounded in $W^{-1,\infty}$.

On the other hand, $\operatorname{curl} u^{\varepsilon}$ is compact in $W^{-1,p}$ for some 1 . By the interpolation theorem,

$$\operatorname{curl} u^{\varepsilon}$$
 is compact in H_{loc}^{-1} . (2.7)

For a fixed compact set K, the density ρ^{ε} can be controlled by $\sup_{\varepsilon} \left(\sup_{x \in K} B^{\varepsilon} / \inf_{x \in K} S^{\varepsilon}\right)^{\frac{1}{\gamma - 1}}$. Similarly, we have

$$\operatorname{div}(\rho^{\varepsilon}u^{\varepsilon})$$
 is compact in H_{loc}^{-1} . (2.8)

Step 3. The strong convergence of $u^{\varepsilon}(x)$, which also leads to the strong convergence of $(\rho^{\varepsilon}, p^{\varepsilon})(x)$ from Step 1. By the div-curl lemma of Murat [26] and Tartar [29], the Young

measure representation theorem for a uniformly bounded sequence of functions (cf. Tartar [29]; also Ball [2]), and (2.7)–(2.8), we have the following commutation identity:

$$\sum_{i=1}^{n} \langle \nu(u), \, \rho(q)u_i \rangle \langle \nu(u), u_i \rangle = \langle \nu(u), \, \sum_{i=1}^{n} \rho(q)u_i u_i \rangle. \tag{2.9}$$

Here and hereafter, for simplicity of notation, we have used that $\nu(u) := \nu_x(\rho(q; \overline{B}(x), \overline{S}(x)), u)$ denotes the associated Young measure (a probability measure) for the sequence $u^{\varepsilon}(x)$, and $\rho(q) := \rho(q; \overline{B}(x), \overline{S}(x))$ for the limits $\overline{B}(x)$ and $\overline{S}(x)$ of $B^{\varepsilon}(x)$ and $S^{\varepsilon}(x)$ respectively.

Then the main point in this step for the compensated compactness framework is to prove that ν is in fact a Dirac measure, which in turn implies the compactness of the sequence $u^{\varepsilon}(x)$.

Combining both sides of (2.9) together, we have

$$\langle \nu(u^{(1)}) \otimes \nu(u^{(2)}), \sum_{i=1}^{n} \rho(q^{(1)}) u_i^{(1)} (u_i^{(1)} - u_i^{(2)}) \rangle = 0.$$
 (2.10)

Exchanging indices (1) and (2), we obtain the following symmetric commutation identity:

$$\langle \nu(u^{(1)}) \otimes \nu(u^{(2)}), I(u^{(1)}, u^{(2)}) \rangle = 0,$$
 (2.11)

where

$$I(u^{(1)}, u^{(2)}) = \sum_{i=1}^{n} (\rho(q^{(1)})u_i^{(1)} - \rho(q^{(2)})u_i^{(2)})(u_i^{(1)} - u_i^{(2)}).$$
(2.12)

Then it remains to prove the strong convergence of the velocity u^{ε} from the above identity. Notice that

$$I(u^{(1)}, u^{(2)}) = \sum_{i=1}^{n} \left(\rho(q^{(1)}) u_i^{(1)} - \rho(q^{(2)}) u_i^{(2)} \right) \left(u_i^{(1)} - u_i^{(2)} \right)$$

$$= \sum_{i=1}^{n} \left(\rho(q^{(1)}) |u_i^{(1)}|^2 - \rho(q^{(1)}) u_i^{(1)} u_i^{(2)} - \rho(q^{(2)}) u_i^{(2)} u_i^{(1)} - \rho(q^{(2)}) |u_i^{(2)}|^2 \right)$$

$$= \rho(q^{(1)}) \left((q^{(1)})^2 - \sum_{i=1}^{n} u_i^{(1)} u_i^{(2)} \right) + \rho(q^{(2)}) \left((q^{(2)})^2 - \sum_{i=1}^{n} u_i^{(1)} u_i^{(2)} \right). \tag{2.13}$$

The Cauchy inequality implies

$$I(u^{(1)}, u^{(2)}) \ge \rho(q^{(1)}) ((q^{(1)})^2 - q^{(1)}q^{(2)}) + \rho(q^{(2)}) ((q^{(2)})^2 - q^{(1)}q^{(2)})$$

$$= (q^{(1)} - q^{(2)}) (\rho(q^{(1)})q^{(1)} - \rho(q^{(2)})q^{(2)})$$

$$= (q^{(1)} - q^{(2)})^2 \frac{d(\rho q)}{dq} (\tilde{q}), \qquad (2.14)$$

where \tilde{q} lies between $q^{(1)}$ and $q^{(2)}$ by the mean-value theorem.

Taking derivative with respect to q on (2.4), we obtain

$$\frac{d\rho}{dq} = -\frac{q}{(\gamma - 1)\rho^{\gamma - 2}\overline{S}} = -\frac{\rho q}{c^2}.$$

Then

$$\frac{d(\rho q)}{dq} = \rho(1 - M^2).$$

For subsonic-sonic flows, i.e., $q^{(1)}, q^{(2)} \leq q_{cr}(\overline{B})$, we have

$$M^2(\tilde{q}) \le 1.$$

On the other hand,

$$\rho(\tilde{q}) \ge \left(\frac{2\overline{B}}{(\gamma+1)\overline{S}}\right)^{\frac{1}{\gamma-1}} \ge 0.$$

Notice that $M^2(\tilde{q}) = 1$ if and only if $q^{(1)} = q^{(2)} = q_{\rm cr}(\overline{B})$, while $\rho(\tilde{q}) = 0$ if and only if $\overline{B} = 0$ and $q^{(1)} = q^{(2)} = q_{\rm cr}(\overline{B})$. Then

$$I(u^{(1)}, u^{(2)}) \ge (q^{(1)} - q^{(2)})^2 \rho(\tilde{q}) (1 - M^2(\tilde{q})) \ge 0.$$
 (2.15)

With (2.11), it implies that

$$q^{(1)} = q^{(2)},$$

which also deduces

$$\rho^{(1)} = \rho^{(2)}, \qquad p^{(1)} = p^{(2)}.$$

Again, using (2.11) and (2.12), we further obtain

$$0 = \langle \nu(u^{(1)}) \otimes \nu(u^{(2)}), I(u^{(1)}, u^{(2)}) \rangle$$

= $\langle \nu(u^{(1)}) \otimes \nu(u^{(2)}), \rho(q^{(1)}) \sum_{i=1}^{n} (u_i^{(1)} - u_i^{(2)})^2 \rangle,$ (2.16)

which immediately implies

$$u^{(1)} = u^{(2)}$$
.

i.e., $\nu(u)$ concentrates on a single point. If this would not be the case, we could suppose to have two different points u and u in the support of ν . Then (u, u), (u, u), (u, u), and (u, u) would be in the support of $\nu \otimes \nu$, which contradicts with $u^{(1)} = u^{(2)}$. Therefore, the Young measure ν is a Dirac measure, which implies the strong convergence of $(\rho^{\varepsilon}, u^{\varepsilon}, p^{\varepsilon})$. This completes the proof.

For the homentropic case, the entropy function S is constant. Then the pressure p may be regarded as a function of the density ρ in $C^1(\mathbb{R}^+ \cup \{0\}) \cap C^2(\mathbb{R}^+)$, which satisfies $p'(\rho) > 0$ and $2p'(\rho) + \rho p''(\rho) > 0$ for $\rho > 0$.

Without loss of generality, we set the enthalpy $h(\rho)$ as

$$h(\rho) := \int_1^{\rho} \frac{p'(s)}{s} ds,$$

so that h(1) = 0. It is noticeable that, in this case, we do not have the property that the Bernoulli function is greater or equal to zero. To replace the nonnegative property, we introduce a lower bound

$$B_{\min} = \lim_{\rho \to 0^+} f(\rho),$$

while

$$f(\rho) := \frac{p'(\rho)}{2} + h(\rho)$$

belongs to $C^1(\mathbb{R}^+ \cup \{0\})$. Since $2p'(\rho) + \rho p''(\rho) > 0$ for $\rho > 0$, $f(\rho)$ is an increase function in $\rho > 0$. Then $f(\rho) > B_{\min}$ for $\rho > 0$ and B_{\min} is lower bound so that $B_{\min} < f(1) = \frac{p'(1)}{2}$.

In the homentropic case, conditions (A.1)–(A.3) can be reformulated as:

(B.1). $M^{\varepsilon} \leq 1$ a.e. in Ω ;

(B.2).
$$B^{\varepsilon} = \frac{(q^{\varepsilon})^2}{2} + \int_1^{\rho^{\varepsilon}} \frac{p'(s)}{s} ds$$
 are uniformly bounded and $B^{\varepsilon} \geq B_{\min}$;

(B.3). curl u^{ε} , $\frac{e_1(\varepsilon)}{\rho^{\varepsilon}}$, and $\frac{e_2(\varepsilon)}{\rho^{\varepsilon}}$ are uniformly bounded measures.

Similar to Theorem 2.1, we have

Theorem 2.2 (Compensated compactness framework for the homentropic case). Let a sequence of functions $\rho^{\varepsilon}(x)$ and $u^{\varepsilon}(x) = (u_1^{\varepsilon}, \dots, u_n^{\varepsilon})(x)$ satisfy conditions (B.1)–(B.3). Then there exists a subsequence (still labeled) $(\rho^{\varepsilon}, u^{\varepsilon})(x)$ such that

$$\rho^{\varepsilon}(x) \to \rho(x), \quad u^{\varepsilon}(x) \to u(x) = (u_1, \cdots, u_n)(x) \quad a.e. \ x \in \Omega \quad as \ \varepsilon \to 0$$

and

$$M(x) \le 1$$
 a.e. $x \in \Omega$.

Proof. First, since $p'(\rho) > 0$ for $\rho > 0$, we can employ the implicit function theorem to conclude $\rho(q;B) = h^{-1}(B - \frac{q^2}{2})$. Then we can regard ρ^{ε} as a function of q^{ε} and B^{ε} , that is, $\rho^{\varepsilon} = \rho(q^{\varepsilon}; B^{\varepsilon})$. As a consequence, the sequence ρ^{ε} is nonnegative and uniformly bounded. Conditions (B.1)–(B.2) indicate directly that the speed sequence q^{ε} is uniformly bounded.

Differentiating the Bernoulli functions B^{ε} with respect to x_i yields

$$\partial_{x_{i}}B^{\varepsilon} = \sum_{j=1}^{n} u_{j}^{\varepsilon} \, \partial_{x_{i}} u_{j}^{\varepsilon} + \frac{p'(\rho^{\varepsilon})}{\rho^{\varepsilon}} \partial_{x_{i}} \rho^{\varepsilon}$$

$$= \sum_{j=1}^{n} u_{j}^{\varepsilon} \, \partial_{x_{i}} u_{j}^{\varepsilon} + \frac{\partial_{x_{i}} p(\rho^{\varepsilon})}{\rho^{\varepsilon}}$$

$$= \sum_{j=1}^{n} u_{j}^{\varepsilon} \, \partial_{x_{i}} u_{j}^{\varepsilon} + \frac{e_{2i}(\varepsilon) - \sum_{j=1}^{n} \rho^{\varepsilon} u_{j}^{\varepsilon} \, \partial_{x_{j}} u_{i}^{\varepsilon} - u_{i}^{\varepsilon} e_{1}(\varepsilon)}{\rho^{\varepsilon}}$$

$$= \sum_{j=1}^{n} u_{j}^{\varepsilon} \, (\partial_{x_{i}} u_{j}^{\varepsilon} - \partial_{x_{j}} u_{i}^{\varepsilon}) + \frac{e_{2i}(\varepsilon) - u_{i}^{\varepsilon} e_{1}(\varepsilon)}{\rho^{\varepsilon}}$$

$$= \sum_{j=1}^{n} u_{j}^{\varepsilon} \, \omega_{ij}^{\varepsilon} + \frac{e_{2i}(\varepsilon) - u_{i}^{\varepsilon} e_{1}(\varepsilon)}{\rho^{\varepsilon}}.$$

$$(2.17)$$

From the boundedness of q^{ε} and condition (B.3), we conclude that

 ∇B^{ε} is uniformly bounded measures.

Since B^{ε} is uniformly bounded, the total-variation norm of B^{ε} is uniformly bounded, which implies that $B^{\varepsilon}(x)$ converges to $\overline{B}(x)$ in L^{1}_{loc} , as ε tends to 0, and $\overline{B}(x) \geq B_{\min}$ a.e. in Ω .

From the definition, $(\operatorname{curl} u^{\varepsilon})_{ij} = \omega_{ij}^{\varepsilon} = \partial_{x_i} u_j^{\varepsilon} - \partial_{x_j} u_i^{\varepsilon}$ is bounded in $W^{-1,\infty}$. On the other hand, $\operatorname{curl} u^{\varepsilon}$ is a uniformly bounded measure sequence, which implies that $\operatorname{curl} u^{\varepsilon}$ is compact in $W^{-1,q}$ for each $1 \leq p < \frac{n}{n-1}$. From the interpolation theorem,

$$\operatorname{curl} u^{\varepsilon}$$
 is compact in H_{loc}^{-1} .

Similarly, we have

$$\operatorname{div}(\rho^{\varepsilon}u^{\varepsilon})$$
 is compact in H_{loc}^{-1} .

Next, we will discuss the strong convergence in two cases.

Case 1: $\overline{B} > B_{\min}$. From the monotonicity of $f(\rho)$, we have

$$\rho_{\rm cr} > 0$$
,

which implies $f(\rho_{cr}) = \overline{B}$ and, on the support of ν ,

$$\rho(q) \in [\rho_{\rm cr}, h^{-1}(\overline{B})].$$

Following similar argument for Theorem 2.1, we obtain the following commutation identity:

$$\langle \nu(u^{(1)}) \otimes \nu(u^{(2)}), I(u^{(1)}, u^{(2)}) \rangle = 0,$$
 (2.18)

and

$$I(u^{(1)}, u^{(2)}) = \sum_{i=1}^{n} \left(\rho(q^{(1)}) u_i^{(1)} - \rho(q^{(2)}) u_i^{(2)} \right) \left(u_i^{(1)} - u_i^{(2)} \right). \tag{2.19}$$

By the same calculation as in the previous argument, we have

$$I(u^{(1)}, u^{(2)}) \ge (q^{(1)} - q^{(2)})^2 \frac{d(\rho q)}{dq}(\tilde{q}),$$
 (2.20)

where \tilde{q} lies between $q^{(1)}$ and $q^{(2)}$.

From the definition of $\rho(q)$, we obtain that $\frac{d\rho}{dq} = -\frac{\rho q}{c^2}$, which implies $\frac{d(\rho q)}{dq} = \rho(1 - M^2)$. From subsonic-sonic flows, *i.e.*, $q^{(1)}$, $q^{(2)} \leq q_{cr}$, we have

$$\rho(\tilde{q})(1 - M^2(\tilde{q})) \ge 0.$$

Notice that $M^2(\tilde{q}) = 1$ if and only if $q^{(1)} = q^{(2)} = q_{\rm cr}$. Then

$$I(u^{(1)}, u^{(2)}) \ge (q^{(1)} - q^{(2)})^2 \rho(\tilde{q})(1 - M^2(\tilde{q})) \ge 0.$$
 (2.21)

Thus, from (2.18), we obtain

$$q^{(1)} = q^{(2)}.$$

Again using (2.18) and (2.19), we have

$$0 = \langle \nu(u^{(1)}) \otimes \nu(u^{(2)}), I(u^{(1)}, u^{(2)}) \rangle$$

= $\langle \nu(u^{(1)}) \otimes \nu(u^{(2)}), \rho(q^{(1)}) \sum_{i=1}^{n} (u_i^{(1)} - u_i^{(2)})^2 \rangle,$ (2.22)

which immediately implies $u^{(1)} = u^{(2)}$, *i.e.*, the Young measure ν is a Dirac measure. Thus, we conclude the strong convergence of $(\rho^{\varepsilon}, u^{\varepsilon})(x)$ to $(\rho, u)(x)$ with $M(x) \leq 1$ a.e $x \in \Omega$.

Case 2. $\overline{B} = B_{\min}$. Considering the boundedness of \overline{B} , we can see $\lim_{\rho \to 0^+} \int_1^{\rho} \frac{p'(s)}{s} ds$ is finite, which implies p'(0) = 0. On the other hand, the monotonicity of $f(\rho)$ shows that $\rho(q) = 0$ for any q belonging to the support of the Young measure ν . It follows from the subsonic-sonic condition that $0 \le q^2 \le p'(0) = 0$. Then the strong convergence of $(\rho^{\varepsilon}, u^{\varepsilon})$ is shown in this case.

Remark 2.1. The main difference between Theorems 2.1 and 2.2 is that the homentropic case has the Bernoulli-vortex relation (2.17), while the full Euler case has

$$\partial_{x_i} B^{\varepsilon} = \sum_{j=1}^n u_j^{\varepsilon} \omega_{ij}^{\varepsilon} + \frac{(\rho^{\varepsilon})^{\gamma - 1}}{\gamma} \partial_{x_i} S^{\varepsilon} + \frac{e_{2i}(\varepsilon) - u_i^{\varepsilon} e_1(\varepsilon)}{\rho^{\varepsilon}}$$
(2.23)

so that the gradient of B^{ε} cannot be achieved only by the vorticity ω^{ε} .

Remark 2.2. The main theorem in Huang-Wang-Wang [23] is included in Theorem 2.2. Condition (B.1) is the same as the one in [23], while B^{ε} is assumed to be constant in [23] which clearly satisfies condition (B.2). As a consequence, condition (B.3) could be regarded as the H_{loc}^{-1} -compactness of curlu $^{\varepsilon}$. The irrotational condition in [23] is removed. Thus, Theorem 2.2 includes more physical consideration. From (2.17), the irrotational condition implies that the Bernoulli function is a constant in the flow field.

Remark 2.3. Consider any function $Q(\rho, u, p) = (Q_1, \dots, Q_n)(\rho, u, p)$ satisfying

$$\operatorname{div}\left(Q(\rho^{\varepsilon}, u^{\varepsilon}, p^{\varepsilon})\right) = o_{Q}(\varepsilon), \tag{2.24}$$

where $o_Q(\varepsilon) \to 0$ in the distributional sense as $\varepsilon \to 0$. We can see from the strong convergence of $(\rho^{\varepsilon}, u^{\varepsilon}, p^{\varepsilon})$ ensured by Theorem 2.1 that $\operatorname{div}(Q(\rho, u, p)) = 0$ holds in the distributional sense. Thus, if

$$\operatorname{div}\left(\rho^{\varepsilon}u^{\varepsilon}\otimes u^{\varepsilon}+p^{\varepsilon}I\right)=e_{2}(\varepsilon)\to0\qquad \text{in the sense of distributions},\tag{2.25}$$

the weak solution also satisfies the momentum equations in $(1.1)_2$ and the energy equation $(1.1)_3$ in the distributional sense. The statement is also valid for Theorem 2.2.

Then, as corollaries, we conclude the following theorems.

Theorem 2.3 (Convergence of approximate solutions for the full Euler flow). Let $\rho^{\varepsilon}(x)$, $u^{\varepsilon}(x) = (u_1^{\varepsilon}, \dots, u_n^{\varepsilon})(x)$, and $p^{\varepsilon}(x)$ be a sequence of approximate solutions satisfying (A.1)–(A.3) and $e_j(\varepsilon) \to 0, j = 1, 2, 3$, in the distributional sense as $\varepsilon \to 0$. Then there exists a subsequence (still labeled) $(\rho^{\varepsilon}, u^{\varepsilon}, p^{\varepsilon})(x)$ that converges a.e. as $\varepsilon \to 0$ to a weak solution (ρ, u, p) to the Euler equations of (1.1), which satisfies $M(x) \leq 1$, a.e. $x \in \Omega$.

Theorem 2.4 (Convergence of approximate solutions for the homentropic Euler flow). Let $\rho^{\varepsilon}(x)$ and $u^{\varepsilon}(x) = (u_1^{\varepsilon}, \dots, u_n^{\varepsilon})(x)$ be a sequence of approximate solutions satisfying (B.1)–(B.3) and $e_j(\varepsilon) \to 0, j = 1, 2$, in the distributional sense as $\varepsilon \to 0$. Then there exists a subsequence (still labeled) $(\rho^{\varepsilon}, u^{\varepsilon})(x)$ that converges a.e. as $\varepsilon \to 0$ to a weak solution (ρ, u) to the Euler equations of (1.5), which satisfies $M(x) \le 1$ a.e. $x \in \Omega$.

There are various ways to construct approximate solutions by either numerical methods or analytical methods such as vanishing viscosity methods. As direct applications, we show two examples in Sections 3–4 to apply the compactness framework built above in establishing existence theorems for multidimensional subsonic-sonic full Euler flows through infinitely long nozzles.

3. Subsonic-Sonic Limit for Two-Dimensional Steady Full Euler Flows in an Infinitely Long Nozzle

In this section, as a direct application of the compactness framework established in Theorem 2.1, we obtain the subsonic-sonic limit of steady subsonic full Euler flows in a two-dimensional, infinitely long nozzle.

The infinitely long nozzle is defined as

$$\Omega = \{(x_1, x_2) : f_1(x_1) < x_2 < f_2(x_1), -\infty < x_1 < \infty\},$$

with the nozzle walls $\partial \Omega := W_1 \cup W_2$, where

$$W_i = \{(x_1, x_2) : x_2 = f_i(x_1) \in C^{2,\alpha}, -\infty < x_1 < \infty\}, \quad i = 1, 2.$$

Suppose that W_1 and W_2 satisfy

$$f_2(x_1) > f_1(x_1) \quad \text{for } x_1 \in (-\infty, \infty),$$

$$f_1(x_1) \to 0, \quad f_2(x_1) \to 1 \quad \text{as } x_1 \to -\infty,$$

$$f_1(x_1) \to a, \quad f_2(x_1) \to b > a \quad \text{as } x_1 \to \infty,$$

$$(3.1)$$

and there exists $\alpha > 0$ such that

$$||f_i||_{C^{2,\alpha}(\mathbb{R})} \le C, \qquad i = 1, 2,$$
 (3.2)

for some positive constant C. It follows that Ω satisfies the uniform exterior sphere condition with some uniform radius r > 0. See Fig 3.1.

Suppose that the nozzle has impermeable solid walls so that the flow satisfies the slip boundary condition:

$$u \cdot \nu = 0$$
 on $\partial \Omega$, (3.3)

where $u = (u_1, u_2) \in \mathbb{R}^2$ is the velocity and $\nu = (\nu_1, \nu_2)$ is the unit outward normal to the nozzle wall. In the flow without vacuum, it can be written as

$$(\rho u) \cdot \nu = 0$$
 on $\partial \Omega$. (3.4)




FIGURE 3.1. Two-Dimensional Infinitely Long Nozzle

It follows from $(1.1)_1$ and (3.4) that

$$\int_{S} (\rho u) \cdot l \, ds \equiv m \tag{3.5}$$

holds for some constant m, which is the mass flux, where s is any curve transversal to the x_1 -direction, and l is the normal of s in the positive x_1 -axis direction.

We assume that the upstream entropy function is given, i.e.,

$$\frac{\gamma p}{(\gamma - 1)\rho^{\gamma}} \longrightarrow S_{-}(x_2) \quad \text{as } x_1 \to -\infty, \tag{3.6}$$

and the upstream Bernoulli function is given, i.e.,

$$\frac{q^2}{2} + \frac{\gamma p}{(\gamma - 1)\rho} \longrightarrow B_-(x_2) \quad \text{as } x_1 \to -\infty, \tag{3.7}$$

where $B(x_2)$ is a function defined on [0,1].

Problem 1(m): Solve the full Euler system (1.1) with the boundary condition (3.4), the mass flux condition (3.5), and the asymptotic conditions (3.6)–(3.7).

Set

$$\underline{S} = \inf_{x_2 \in [0,1]} S_-(x_2), \qquad \underline{B} = \inf_{x_2 \in [0,1]} B_-(x_2).$$

For this problem, the following theorem has been established in Chen-Deng-Xiang [7].

Theorem 3.1. Let the nozzle walls $\partial\Omega$ satisfy (3.1)-(3.2), and let $\underline{S} > 0$ and $\underline{B} > 0$. Then there exists $\delta_0 > 0$ such that, if $\|(S_- - \underline{S}, B_- - \underline{B})\|_{C^{1,1}([0,1])} \le \delta$ for $0 < \delta \le \delta_0$, $(S_- B_-^{-\gamma})'(0) \ge 0$, and $(S_- B_-^{-\gamma})'(1) \le 0$, there exists $\hat{m} \ge 2\delta_0^{1/8}$ such that, for any $m \in (\delta^{1/4}, \hat{m})$, there exists a global solution (i.e. a full Euler flow) $(\rho, u, p) \in C^{1,\alpha}(\overline{\Omega})$ of **Problem 1**(m) such that the following hold:

(i) Subsonicity and positivity of the horizontal velocity: The flow is uniformly subsonic with positive horizontal velocity in the whole nozzle, i.e.,

$$\sup_{\overline{\Omega}}(q^2 - c^2) < 0, \quad u_1 > 0 \quad in \overline{\Omega}; \tag{3.8}$$

(ii) The flow satisfies the following asymptotic behavior in the far fields: As $x_1 \to -\infty$,

$$p \to p_{-} > 0, \qquad u_1 \to u_{-}(x_2) > 0, \qquad (u_2, \rho) \to (0, \rho_{-}(x_2; p_{-})),$$
 (3.9)

$$\nabla p \to 0, \quad \nabla u_1 \to (0, u'_-(x_2)), \quad \nabla u_2 \to 0, \quad \nabla \rho \to (0, \rho'_-(x_2; p_-))$$
 (3.10)

uniformly for $x_2 \in K_1 \in (0,1)$, where $\rho_-(x_2; p_-) = \left(\frac{\gamma p_-}{(\gamma - 1)S_-(x_2)}\right)^{1/\gamma}$, the constant p_- and function $u_-(x_2)$ can be determined by m, $S_-(x_2)$, and $B_-(x_2)$ uniquely;

(iii) Uniqueness: The full Euler flow of **Problem 1**(m) satisfying (3.8) and the asymptotic behavior (3.9)–(3.10) is unique.

(iv) Critical mass flux: \hat{m} is the upper critical mass flux for the existence of subsonic flow in the following sense: Either $\sup_{\overline{\Omega}}(q^2-c^2)\to 0$ as $m\to\hat{m}$, or there is no $\sigma>0$ such that, for all $m\in(\hat{m},\hat{m}+\sigma)$, there are full Euler flows of **Problem 1**(m) satisfying (3.8), the asymptotic behavior (3.9)–(3.10), and $\sup_{m\in(\hat{m},\hat{m}+\sigma)}\sup_{\overline{\Omega}}(c^2-q^2)>0$.

We note that Theorem 3.1 does not apply to the critical flows, that is, those flows for which $m = \hat{m}$ must be sonic at some point. Now we can employ Theorem 2.1 to establish a more general result.

Theorem 3.2 (Subsonic-sonic limit of two-dimensional full Euler flows). Let $\delta^{1/4} < m^{\varepsilon} < \hat{m}$ be a sequence of mass fluxes, and let $(\rho^{\varepsilon}, u^{\varepsilon}, p^{\varepsilon})(x)$ be the corresponding sequence of solutions to **Problem 1** (m^{ε}) . Then, as $m^{\varepsilon} \to \hat{m}$, the solution sequence possesses a subsequence (still denoted by) $(\rho^{\varepsilon}, u^{\varepsilon}, p^{\varepsilon})(x)$ that converges strongly a.e. in Ω to a vector function $(\rho, u, p)(x)$ which is a weak solution of **Problem 1** (\hat{m}) . Furthermore, the limit solution $(\rho, u, p)(x)$ also satisfies (1.1) in the distributional sense and the boundary conditions (3.4) as the normal trace of the divergence-measure field ρu on the boundary in the sense of Chen-Frid [8].

Proof. We divide the proof into three steps.

1. We first need to show that $(\rho^{\varepsilon}, u^{\varepsilon}, p^{\varepsilon})(x)$ satisfy condition (A.1)–(A.3). For B^{ε} and S^{ε} , we have

$$\begin{cases} \partial_{x_1}(\rho^{\varepsilon}u_1^{\varepsilon}) + \partial_{x_2}(\rho^{\varepsilon}u_2^{\varepsilon}) = 0, \\ \partial_{x_1}(\rho^{\varepsilon}u_1^{\varepsilon}B^{\varepsilon}) + \partial_{x_2}(\rho^{\varepsilon}u_2^{\varepsilon}B^{\varepsilon}) = 0, \\ \partial_{x_1}(\rho^{\varepsilon}u_1^{\varepsilon}S^{\varepsilon}) + \partial_{x_2}(\rho^{\varepsilon}u_2^{\varepsilon}S^{\varepsilon}) = 0. \end{cases}$$

$$(3.11)$$

From $(3.11)_1$, we introduce the following stream function ψ^{ε} :

$$\begin{cases} \partial_{x_1} \psi^{\varepsilon} = -\rho^{\varepsilon} u_2^{\varepsilon}, \\ \partial_{x_2} \psi^{\varepsilon} = \rho^{\varepsilon} u_1^{\varepsilon}, \end{cases}$$
(3.12)

which means that ψ^{ε} is constant along the streamlines.

From the far-field behavior of the Euler flows, we define

$$\psi^{\varepsilon}_{-}(x_2) := \lim_{x_1 \to -\infty} \psi^{\varepsilon}(x_1, x_2).$$

Since both the upstream Bernoulli and entropy functions are given, B^{ε} and S^{ε} have the following expression:

$$B^{\varepsilon}(x) = B_{-}((\psi_{-}^{\varepsilon})^{-1}(\psi^{\varepsilon}(x))), \qquad S^{\varepsilon}(x) = S_{-}((\psi_{-}^{\varepsilon})^{-1}(\psi^{\varepsilon}(x))),$$

where $(\psi_{-}^{\varepsilon})^{-1}\psi^{\varepsilon}(x)$ is a function from Ω to [0,1]. For fixed x_1 , it can be regarded as a backward characteristic map with

$$\frac{\partial((\psi_{-}^{\varepsilon})^{-1}\psi^{\varepsilon})}{\partial x_{2}} = \frac{\rho^{\varepsilon}u_{1}^{\varepsilon}}{\rho_{-}^{\varepsilon}u_{-}^{\varepsilon}} > 0.$$

The boundedness and positivity of $\rho_{-}^{\varepsilon}u_{-}^{\varepsilon}$ and $\rho^{\varepsilon}u_{1}^{\varepsilon}$ show that the map is not degenerate. Thus, we have

$$\begin{cases} \partial_{x_1} B^{\varepsilon}(x) = -B'_{-}((\psi^{\varepsilon}_{-})^{-1}(\psi^{\varepsilon}(x))) \frac{\rho^{\varepsilon} u^{\varepsilon}_{2}}{\rho^{\varepsilon}_{-} u^{\varepsilon}_{-}}, \\ \partial_{x_2} B^{\varepsilon}(x) = B'_{-}((\psi^{\varepsilon}_{-})^{-1}(\psi^{\varepsilon}(x))) \frac{\rho^{\varepsilon} u^{\varepsilon}_{1}}{\rho^{\varepsilon}_{-} u^{\varepsilon}}. \end{cases}$$

$$(3.13)$$

Then B^{ε} is uniformly bounded in BV, which implies its strong convergence. The similar argument can lead to the strong convergence of S^{ε} .

2. For the corresponding vorticity sequence ω^{ε} , (2.23) can be written as

$$\begin{cases} \partial_{x_1} B^{\varepsilon} = u_2^{\varepsilon} \omega^{\varepsilon} + \frac{1}{\gamma} (\rho^{\varepsilon})^{\gamma - 1} \partial_{x_1} S^{\varepsilon}, \\ \partial_{x_2} B^{\varepsilon} = -u_1^{\varepsilon} \omega^{\varepsilon} + \frac{1}{\gamma} (\rho^{\varepsilon})^{\gamma - 1} \partial_{x_2} S^{\varepsilon}. \end{cases}$$
(3.14)

By direct calculation, we have

$$\omega^{\varepsilon} = \frac{1}{(q^{\varepsilon})^{2}} \left(u_{2}^{\varepsilon} \left(\partial_{x_{1}} B^{\varepsilon} - \frac{1}{\gamma} (\rho^{\varepsilon})^{\gamma - 1} \partial_{x_{1}} S^{\varepsilon} \right) - u_{1}^{\varepsilon} \left(\partial_{x_{2}} B^{\varepsilon} - \frac{1}{\gamma} (\rho^{\varepsilon})^{\gamma - 1} \partial_{x_{2}} S^{\varepsilon} \right) \right)$$

$$= \frac{1}{\rho_{-}^{\varepsilon} u_{-}^{\varepsilon}} \left(\rho^{\varepsilon} B_{-}' - \frac{1}{\gamma} (\rho^{\varepsilon})^{\gamma} S_{-}' \right), \tag{3.15}$$

which implies that ω^{ε} as a measure sequence is uniformly bounded, which is compact in H_{loc}^{-1}

Then Theorem 2.1 immediately implies that the solution sequence has a subsequence (still denoted by) $(\rho^{\varepsilon}, u^{\varepsilon}, p^{\varepsilon})(x)$ that converges a.e. in Ω to a vector function $(\rho, u, p)(x)$.

Since (1.1) holds for the sequence of subsonic solutions $(\rho^{\varepsilon}, u^{\varepsilon}, p^{\varepsilon})(x)$, it is straightforward to see that (ρ, u, p) also satisfies (1.1) in the distributional sense.

3. The boundary condition is satisfied in the sense of Chen-Frid [8], which implies

$$\int_{\partial\Omega} \phi(w)(\rho u)(w) \cdot \nu(w) \, d\mathcal{H}^1(w) = \int_{\Omega} (\rho u)(x) \cdot \nabla \phi(x) \, dx + \langle \operatorname{div}(\rho u)|_{\Omega}, \phi \rangle \tag{3.16}$$

for $\psi \in \mathbf{C}_0^1$. From above, we can see that $\langle \operatorname{div}(\rho u)|_{\Omega}, \phi \rangle = 0$. Also,

$$\int_{\Omega} (\rho u)(x) \cdot \nabla \phi(x) \, dx = \lim_{\varepsilon \to 0} \int_{\Omega} (\rho^{\varepsilon} u^{\varepsilon})(x) \cdot \nabla \phi(x) \, dx = 0. \tag{3.17}$$

Then we have

$$\int_{\partial\Omega} \phi(w)(\rho u)(w) \cdot \nu(w) d\mathcal{H}^{1}(w) = 0, \tag{3.18}$$

that is, $(\rho u) \cdot \nu = 0$ on $\partial \Omega$ in \mathcal{D}' .

This completes the proof.

4. Subsonic-Sonic Limit for the Full Euler Flows in an Infinitely Long Axisymmetric Nozzle

We consider flows though an infinitely long axisymmetric nozzle given by

$$\Omega = \{ (x_1, x_2, x_3) \in \mathbb{R}^3 : 0 \le \sqrt{x_2^2 + x_3^2} < f(x_1), -\infty < x_1 < \infty \},$$

where $f(x_1)$ satisfies

$$f(x_1) \to 1 \quad \text{as } x_1 \to -\infty,$$

$$f(x_1) \to r_0 \quad \text{as } x_1 \to \infty,$$

$$\|f\|_{C^{2,\alpha}(\mathbb{R})} \le C \quad \text{for some } \alpha > 0 \text{ and } C > 0,$$

$$\inf_{x_1 \in \mathbb{R}} f(x_1) = b > 0.$$

$$(4.1)$$

See Fig. 4.2.

The boundary condition is set as follows: Since the nozzle wall is solid, the flow satisfies the slip boundary condition:

$$u \cdot \nu = 0$$
 on $\partial \Omega$, (4.3)




FIGURE 4.2. Infinitely Long Axisymmetric Nozzle

where $u = (u_1, u_2, u_3)$, and $\nu = (\nu_1, \nu_2, \nu_3)$ is the unit outward normal to the nozzle wall. In the flow without vacuum, it can be written as

$$(\rho u) \cdot \nu = 0$$
 on $\partial \Omega$. (4.4)

The continuity equation in $(1.1)_1$ and the boundary condition (4.4) imply that the mass flux

$$\int_{\Sigma} (\rho u) \cdot l \, ds \equiv m_0 \tag{4.5}$$

remains for some positive constant m_0 , where Σ is any surface transversal to the x_1 -axis direction, and l is the normal of Σ in the positive x_1 -axis direction.

In Duan-Luo [19], the axisymmetric flows without swirl are considered for the fluid density $\rho = \rho(x_1, r)$, the velocity

$$u = (u_1, u_2, u_3) = (U(x_1, r), V(x_1, r) \frac{x_2}{r}, V(x_1, r) \frac{x_3}{r}),$$

and the pressure $p = p(x_1, r)$ in the cylindrical coordinates, where u_1, u_2, u_3 are the axial velocity, radial velocity, and swirl velocity, respectively, and $r = \sqrt{x_2^2 + x_3^2}$. Then, instead of (1.1), we have

$$\begin{cases}
\partial_{x_1}(r\rho U) + \partial_r(r\rho V) = 0, \\
\partial_{x_1}(r\rho U^2) + \partial_r(r\rho UV)_r + r\partial_{x_1}p = 0, \\
\partial_{x_1}(r\rho UV) + \partial_r(r\rho V^2)_r + r\partial_r p = 0, \\
\partial_{x_1}(r\rho U(E + \frac{p}{\rho})) + \partial_r(r\rho V(E + \frac{p}{\rho})) = 0.
\end{cases} (4.6)$$

Rewrite the axisymmetric nozzle as

$$\Omega = \{ (x_1, r) : 0 \le r < f(x_1), -\infty < x_1 < \infty \}$$

with the boundary of the nozzle:

$$\partial \Omega = \{(x_1, r) : r = f(x), -\infty < x_1 < \infty\}.$$

The boundary condition (4.3) becomes

$$(U, V, 0) \cdot \tilde{\nu} = 0$$
 on $\partial \Omega$, (4.7)

where $\tilde{\nu}$ is the unit outer normal of the nozzle walls in the cylindrical coordinates. The mass flux condition (4.5) can be rewritten in the cylindrical coordinates as

$$\int_{\Sigma} (r\rho U, r\rho V, 0) \cdot l \, dS \equiv m := \frac{m_0}{2\pi},\tag{4.8}$$

where Σ is any curve transversal to the x_1 -axis direction, and l is the unit normal of Σ .

The quantities $B = h(\rho, p) + \frac{U^2 + V^2}{2}$ and $S = \frac{\gamma p}{(\gamma - 1)\rho^{\gamma}}$ are both constants along each streamline. For the full Euler flows in the axisymmetric nozzle, we assume that the upstream Bernoulli and entropy functions are given, that is,

$$h(\rho, p) + \frac{U^2 + V^2}{2} \longrightarrow B_-(r)$$
 as $x_1 \to -\infty$, (4.9)

$$\frac{\gamma p}{(\gamma - 1)\rho^{\gamma}} \longrightarrow S_{-}(r) \quad \text{as } x_1 \to -\infty,$$
 (4.10)

where $B_{-}(r)$ and $S_{-}(r)$ are smooth functions defined on [0, 1].

Set

$$\underline{B} = \inf_{r \in [0,1]} B_{-}(r), \quad \sigma_1 = \|B'_{-}\|_{C^{0,1}([0,1])}, \tag{4.11}$$

$$\underline{S} = \inf_{r \in [0,1]} S_{-}(r), \quad \sigma_2 = ||S'_{-}||_{C^{0,1}([0,1])}. \tag{4.12}$$

We denote the above problem as **Problem 2**(m). It is shown in [19] that

Theorem 4.1. Suppose that the nozzle satisfies (4.1). Let the upstream Bernoulli function $B_{-}(r)$ and entropy function $S_{-}(r)$ satisfy $\underline{B} > 0$, $B'_{-}(r) \in C^{1,1}([0,1])$, $B'_{-}(0) = 0$, $B'_{-}(r) \geq 0$ on $r \in [0,1]$; and S > 0, $S'_{-}(r) \in C^{1,1}([0,1])$, $S'_{-}(0) = 0$, $S'_{-}(r) \leq 0$ on $r \in [0,1]$. Then

(i) There exists $\delta_0 > 0$ such that, if $\delta := \max\{\sigma_1, \sigma_2\} \leq \delta_0$, then there is $\hat{m} \leq 2\delta_0^{1/8}$ so that, for any $m \in (\delta^{1/4}, \hat{m})$, there exists a global C^1 -solution (i.e. a full Euler flow) $(\rho, U, V, p) \in C^1(\overline{\Omega})$ through the nozzle with mass flux condition (4.8) and the upstream asymptotic condition (4.9). Moreover, the flow is uniformly subsonic, and the axial velocity is always positive, i.e.,

$$\sup_{\overline{\Omega}}(U^2 + V^2 - c^2) < 0 \quad and \quad U > 0 \quad in \overline{\Omega}. \tag{4.13}$$

(ii) The subsonic flow satisfies the following properties: As $x_1 \to -\infty$,

$$\rho \to \rho_{-} > 0, \qquad \nabla \rho \to 0, \qquad p \to \frac{\gamma - 1}{\gamma} S_{-}(r) \rho_{-}^{\gamma}, \qquad \nabla p \to (0, \frac{\gamma - 1}{\gamma} S_{-}'(r) \rho_{-}^{\gamma}),$$

$$(U, V) \to (U_{-}(r), 0), \qquad \nabla U \to (0, U_{-}'(r)), \qquad \nabla V \to 0$$

$$(4.14)$$

uniformly for $r \in K_1 \subseteq (0,1)$, where ρ_- is a positive constant, and ρ_- and $U_-(r)$ can be determined by m, $B_-(r)$, and $S_-(r)$ uniquely.

- (iii) There exists at most one smooth axisymmetric subsonic flow through the nozzle which satisfies (4.13) and the properties in (ii).
- (iv) There exists a critical mass flux \hat{m} such that, for any $m \in (\delta^{1/4}, \hat{m})$, there exists a unique axisymmetric subsonic flow through the nozzle with the mass flux condition (4.8) and the asymptotic behavior (4.14). Moreover, \hat{m} is the upper critical mass flux for the existence of subsonic flow in the following sense: Either $\sup(U^2 + V^2 c^2) \to 0$ as $m \to \hat{m}$, or

there is no $\sigma > 0$ such that, for all $m \in (\hat{m}, \hat{m} + \sigma)$, there is an Euler flow with the mass flux m through the nozzle which satisfies the upstream asymptotic condition (4.9)–(4.10), the downstream asymptotic behavior (4.14), and $\sup_{m \in (\hat{m}, \hat{m} + \sigma)} \sup_{\overline{\Omega}} (c^2 - (U^2 + V^2)) > 0.$

As above, we have the subsonic-sonic limit theorem for this case.

Theorem 4.2 (Subsonic-sonic limit of three-dimensional Euler flows through an axisymmetric nozzle). Let $\delta^{1/4} < m^{\varepsilon} < \hat{m}$ be a sequence of mass fluxes, and let ρ^{ε} , $u^{\varepsilon} = (u_1^{\varepsilon}, u_2^{\varepsilon}, u_3^{\varepsilon})$, and p^{ε} be the corresponding solutions to **Problem 2** (m^{ε}) . Then, as $m^{\varepsilon} \to \hat{m}$, the solution sequence possesses a subsequence (still denoted by) $(\rho^{\varepsilon}, u^{\varepsilon}, p^{\varepsilon})$ that converges strongly a.e. in Ω to a vector function (ρ, u, p) with $u = (u_1, u_2, u_3)$ which is a weak solution of **Problem 2** (\hat{m}) . Furthermore, the limit solution (ρ, u, p) also satisfies (1.1) in the distributional sense and the boundary conditions (3.4) as the normal trace of the divergence-measure field $(\rho u_1, \rho u_2, \rho u_3)$ on the boundary in the sense of Chen-Frid [8].

Proof. First, we need to show that $(\rho^{\varepsilon}, u^{\varepsilon}, p^{\varepsilon})$ satisfy condition (A.1)–(A.3) in Ω .

For the approximate solutions, B^{ε} and S^{ε} satisfy

$$\partial_{x_1}(r\rho^{\varepsilon}U^{\varepsilon}B^{\varepsilon}) + \partial_r(r\rho^{\varepsilon}V^{\varepsilon}B^{\varepsilon}) = 0, \tag{4.15}$$

$$\partial_{x_1}(r\rho^{\varepsilon}U^{\varepsilon}S^{\varepsilon}) + \partial_r(r\rho^{\varepsilon}V^{\varepsilon}S^{\varepsilon}) = 0. \tag{4.16}$$

From $\partial_{x_1}(r\rho^{\varepsilon}U^{\varepsilon}) + \partial_r(r\rho^{\varepsilon}V^{\varepsilon}) = 0$, we introduce ψ^{ε} as

$$\begin{cases} \partial_{x_1} \psi^{\varepsilon} = -r \rho^{\varepsilon} V^{\varepsilon}, \\ \partial_r \psi^{\varepsilon} = r \rho^{\varepsilon} U^{\varepsilon}. \end{cases}$$

$$(4.17)$$

From the far-field behavior of the Euler flows, we define $\psi_-^{\varepsilon}(r) := \lim_{x_1 \to -\infty} \psi^{\varepsilon}(x_1, r)$. Similar to the argument in Theorem 3.2, $(\psi_-^{\varepsilon})^{-1}(\psi^{\varepsilon})$ are nondegenerate maps. A direct calculation yields

$$B^{\varepsilon}(x_1, x_2, x_3) = B_{-}((\psi_{-}^{\varepsilon})^{-1}(\psi^{\varepsilon}(x_1, \sqrt{x_2^2 + x_3^2})))$$

$$S^{\varepsilon}(x_1, x_2, x_3) = S_{-}((\psi_{-}^{\varepsilon})^{-1}(\psi^{\varepsilon}(x_1, \sqrt{x_2^2 + x_3^2}))).$$

Therefore, we have

$$\begin{cases} \partial_{x_1} B^{\varepsilon} = -r \rho^{\varepsilon} V^{\varepsilon} \frac{B'_{-}}{(\psi^{\varepsilon}_{-})'}, \\ \partial_{x_2} B^{\varepsilon} = x_2 \rho^{\varepsilon} U^{\varepsilon} \frac{B'_{-}}{(\psi^{\varepsilon}_{-})'}, \\ \partial_{x_3} B^{\varepsilon} = x_3 \rho^{\varepsilon} U^{\varepsilon} \frac{B'_{-}}{(\psi^{\varepsilon}_{-})'}. \end{cases}$$

$$(4.18)$$

Notice that

$$\frac{B'_{-}}{(\psi^{\varepsilon}_{-})'}((\psi^{\varepsilon}_{-})^{-1}(\psi^{\varepsilon})) = \frac{B'_{-}((\psi^{\varepsilon}_{-})^{-1}(\psi^{\varepsilon}))}{(\psi^{\varepsilon}_{-})^{-1}(\psi^{\varepsilon})\rho^{\varepsilon}_{-}U^{\varepsilon}_{-}((\psi^{\varepsilon}_{-})^{-1}(\psi^{\varepsilon}))}.$$
(4.19)

Since $B'_{-}(0) = 0$ and $B_{-} \in C^{1,1}$, we conclude that $\frac{B'_{-}(s)}{s}$ is bounded. Then the sequence B^{ε} is uniformly bounded in BV, which implies its strong convergence. The similar argument can lead to the strong convergence of S^{ε} .

On the other hand, the vorticity ω^{ε} has the following expression:

$$\begin{cases}
\omega_{1,2}^{\varepsilon} = \partial_{x_1} u_2^{\varepsilon} - \partial_{x_2} u_1^{\varepsilon} = \frac{x_2}{r} (\partial_{x_1} V^{\varepsilon} - \partial_r U^{\varepsilon}), \\
\omega_{2,3}^{\varepsilon} = \partial_{x_2} u_3^{\varepsilon} - \partial_{x_3} u_2^{\varepsilon} = 0, \\
\omega_{3,1}^{\varepsilon} = \partial_{x_3} u_1^{\varepsilon} - \partial_{x_1} u_3^{\varepsilon} = -\frac{x_3}{r} (\partial_{x_1} V^{\varepsilon} - \partial_r U^{\varepsilon}).
\end{cases}$$
(4.20)

A direct computation gives

$$\partial_{x_1} V^{\varepsilon} - \partial_r U^{\varepsilon} = \frac{r}{(\psi_{-}^{\varepsilon})'} \left(\rho^{\varepsilon} B'_{-} - \frac{(\rho^{\varepsilon})^{\gamma} S'_{-}}{\gamma} \right), \tag{4.21}$$

which implies that ω^{ε} is uniformly bounded in the bounded measure space.

Since (1.1) holds for the sequence of subsonic solutions $(\rho^{\varepsilon}, u^{\varepsilon}, p^{\varepsilon})(x)$, it is straightforward to see from Theorem 2.1 that there exists a subsequence (still denoted by) $(\rho^{\varepsilon}, u^{\varepsilon}, p^{\varepsilon})$ which converges to a vector function (ρ, u, p) a.e. in Ω satisfying (1.1) in the distributional sense.

The boundary condition is satisfied in the sense of Chen-Frid [8], which implies

$$\int_{\partial\Omega} \phi(w)(\rho u)(w) \cdot \nu(w) \, d\mathcal{H}^1(w) = \int_{\Omega} (\rho u)(x) \cdot \nabla \phi(x) \, dx + \langle \operatorname{div}(\rho u)|_{\Omega}, \phi \rangle \tag{4.22}$$

for $\psi \in \mathbf{C}_0^1$. From above, we can see $\langle \operatorname{div}(\rho u)|_{\Omega}, \phi \rangle = 0$. Furthermore, we have

$$\int_{\Omega} (\rho u)(x) \cdot \nabla \phi(x) \, dx = \lim_{\varepsilon \to 0} \int_{\Omega} (\rho^{\varepsilon} u^{\varepsilon})(x) \cdot \nabla \phi(x) \, dx = 0, \tag{4.23}$$

which yields

$$\int_{\partial\Omega} \phi(w)(\rho u)(w) \cdot \nu(w) d\mathcal{H}^1(w) = 0, \tag{4.24}$$

that is, $(\rho u) \cdot \nu = 0$ on $\partial \Omega$ in \mathcal{D}' .

This completes the proof.

Remark 4.1. In the homentropic case, the subsonic results of [5, 17, 32] can be also extended to the subsonic-sonic limit by using Theorem 2.2.

Acknowledgments: The research of Gui-Qiang Chen was supported in part by the UK EP-SRC Science and Innovation Award to the Oxford Centre for Nonlinear PDE (EP/E035027/1), the NSFC under a joint project Grant 10728101, and the Royal Society-Wolfson Research Merit Award (UK). The research of Fei-Min Huang was supported in part by NSFC Grant No. 10825102 for distinguished youth scholars, and the National Basic Research Program of China (973 Program) under Grant No. 2011CB808002. The research of Tian-Yi Wang was supported in part by the China Scholarship Council No. 201204910256 as an exchange graduate student at the University of Oxford, the UK EPSRC Science and Innovation Award to the Oxford Centre for Nonlinear PDE (EP/E035027/1), and the NSF of China under Grant 11371064.

References

- M. Bae, Stability of contact discontinuity for steady Euler system in the infinite duct, Z. Angew Math. Phys. 64 (2013), 917–936.
- [2] J. Ball, A version of the fundamental theorem of Young measures, In: PDEs and Continuum Models of Phase Transitions, pp. 207–215, Lecture Notes in Physics, 344, Springer-Verlag, 1989.
- [3] L. Bers, Existence and uniqueness of a subsonic flow past a given profile, Comm. Pure Appl. Math. 7 (1954), 441–504.
- [4] L. Bers, Mathematical Aspects of Subsonic and Transonic Gas Dynamics, John Wiley & Sons, Inc.: New York; Chapman & Hall, Ltd.: London, 1958.
- [5] C. Chen and C.-J. Xie, Existence of steady subsonic Euler flows through infinitely long periodic nozzles, J. Diff. Eqs. 252 (2012), 4315–4331.
- [6] G.-Q. Chen, Euler Equations and Related Hyperbolic Conservation Laws, In: Handbook of Differential Equations, Chapter 1, Vol. 2, Eds. C. M. Dafermos, E. Feireisl, Amsterdam: Elsevier Science B.V, pp. 1–104, 2006.
- [7] G.-Q. Chen, X. Deng, and W. Xiang, Global steady subsonic flows through infinitely long nozzles for the full Euler equations, SIAM J. Math. Anal. 44 (2012), 2888–2919.
- [8] G.-Q. Chen and H. Frid, Divergence-measure fields and hyperbolic conservation laws, Arch. Rational Mech. Anal. 147 (1999), 89–118.
- [9] G.-Q. Chen, C. M. Dafermos, M. Slemrod, and D.-H. Wang, On two-dimensional sonic-subsonic flow, Commun. Math. Phys. 271 (2007), 635–647.
- [10] G.-Q. Chen, M. Slemrod, and D.-H. Wang, Vanishing viscosity method for transonic flow, Arch. Rational Mech. Anal. 189 (2008), 159–188.
- [11] S. Chen and H. Yuan, Transonic shocks in compressible flow passing a duct for three-dimensional Euler systems, *Arch. Rational Mech. Anal.* **187** (2008), 523–556.
- [12] R. Courant and K. O. Friedrichs, Supersonic Flow and Shock Waves, Interscience Publishers Inc.: New York, 1948.
- [13] C. M. Dafermos, Hyperbolic Conservation Laws in Continuum Physics, Springer-Verlag: Berlin, 2010.
- [14] R. J. DiPerna, Compensated compactness and general systems of conservation laws, Trans. Amer. Math. Soc. 292 (1985), 383–420.
- [15] G.-C. Dong, Nonlinear Partial Differential Equations of Second Order, AMS: Providence, RI, 1991.
- [16] G.-C. Dong and B. Ou, Subsonic flows around a body in space, Comm. Partial Diff. Eqs. 18 (1993), 355–379.
- [17] L.-L. Du and B. Duan, Global subsonic Euler flows in an infinitely long axisymmetric nozzle, *J. Diff. Eqs.* **250** (2011), 813–847.
- [18] L.-L. Du, Z. Xin, and W. Yan, Subsonic flows in a multidimensional nozzle, *Arch. Rational Mech. Anal.* **201** (2011), 965–1012.
- [19] B. Duan and Z. Luo, Three-dimensional full Euler flows in axisymmetric nozzles, J. Diff. Eqs. 254 (2013), 2705–2731.

- [20] R. Finn and D. Gilbarg, Asymptotic behavior and uniqueness of plane subsonic flows, Comm. Pure Appl. Math. 10 (1957), 23–63.
- [21] R. Finn and D. Gilbarg, Three-dimensional subsonic flows and asymptotic estimates for elliptic partial differential equations, Acta Math. 98 (1957), 265–296.
- [22] F. I. Frankl and M. V. Keldysh, Dieäussere Neumann'she Aufgabe für nichtlineare elliptische differentialgleichungen mit Anwendung auf die Theorie der Flügel im kompressiblen Gas (Russian, German summary), Izeeestiya Akademii Nauk SSR, Series 7 (1934), 561–607.
- [23] F.-M. Huang, T.-Y. Wang, and Y. Wang, On multidimensional sonic-subsonic flow, Acta Math. Sci. Ser. B, 31 (2011), 2131–2140.
- [24] C. S. Morawetz, On a weak solution for a transonic flow problem, Comm. Pure Appl. Math. 38 (1985), 797–818.
- [25] C. S. Morawetz, On steady transonic flow by compensated compactness, Methods Appl. Anal. 2 (1995), 257–268.
- [26] F. Murat, Compacite par compensation, Ann. Suola Norm. Pisa (4), 5 (1978), 489–507.
- [27] D. Serre, Systems of Conservation Laws, Vols. 1–2, Cambridge University Press: Cambridge, 1999, 2000.
- [28] M. Shiffman, On the existence of subsonic flows of a compressible fluid, J. Rational Mech. Anal. 1 (1952), 605–652.
- [29] L. Tartar, Compensated compactness and applications to partial differential equations, In: Nonlinear Analysis and Mechanics: Herriot-Watt Symposium, Vol. 4, Ed. R. J. Knops, Pitman Press, Bostton, Mass.-London, 1979.
- [30] C. Xie and Z. Xin, Global subsonic and subsonic-sonic flows through infinitely long nozzles, *Indiana Univ. Math. J.* 56 (2007), 2991–3023.
- [31] C. Xie and Z. Xin, Global subsonic and subsonic-sonic flows through infinitely long axially symmetric nozzles, *J. Diff. Eqs.* **248** (2010), 2657–2683.
- [32] C. Xie and Z. Xin, Existence of global steady subsonic Euler flows through infinitely long nozzles, SIAM J. Math. Anal. 42 (2010), 751–784.
- G.-Q. Chen, School of Mathematical Sciences, Fudan University, Shanghai 200433, China; Mathematical Institute, University of Oxford, Radcliffe Observatory Quarter, Woodstock Road, Oxford, OX2 6GG, UK; Academy of Mathematics and Systems Science, Academia Sinica, Beijing, 100190, P. R. China

 $E ext{-}mail\ address: chengq@maths.ox.ac.uk}$

F.-M. Huang, Institute of Applied Mathematics, Academy of Mathematics and Systems Science, Academia Sinica, Beijing, 100190, P. R. China

E-mail address: fhuang@amt.ac.cn

T.-Y. Wang, Department of Mathematics, School of Science, Wuhan University of Technology, Wuhan, Hubei, 430070, P. R. China; Academy of Mathematics and Systems Science, Academia Sinica, Beijing, 100190, P. R. China; Mathematical Institute, University of Oxford, Radcliffe Observatory Quarter, Woodstock Road, Oxford, OX2 6GG, UK

 $E ext{-}mail\ address: tianyiwang@whut.edu.cn; wangtianyi@amss.ac.cn}$